












Loadcells

Series (시리즈)	Stroke length (범위)	Rated output (출력)	Linearity (선형성)	Excitation (공급전압)	Repeatability (반복성)	Link
GSO 	10~1000g	1mV/V	±0.05%	10Vdc	±0.05%	GSO
MDB 	2.5~100lbs	2mV/V	±0.05%	10Vdc	±0.05%	MDB
MLP 	10~1000lbs	2mV/V	±0.1%	10Vdc	±0.05%	MLP
SBO 	50~5000lbs	3mV/V	±0.05%	10Vdc	±0.02%	SBO
LPU 	100lbs~50Klbs	3mV/V	±0.1%	10Vdc	±0.05%	LPU
SWP 	1~50klbs	2mV/V	±0.05%	10Vdc	±0.05%	SWP
CLP 	750lbs~200Klbs	2mV/V	±0.5%	10Vdc	±0.15%	CLP

Torque Sensors

Series (시리즈)	Stroke length (범위)	Rated output (출력)	Linearity (선형성)	Excitation (공급전압)	Repeatability (반복성)	Link
TRT 	25 In-lb ~ 100 In-lb	2 mV/V	±0.1%	10Vdc	0.05%	TRT
TRS 	500 In-lb ~ 100K In-lb	2 mV/V	±0.1%	10Vdc	0.05%	TRS



Series (시리즈)	Features (특징)	Link
LSB-200 (L2357) 	<ul style="list-style-type: none"> 오버로드 한계: 1000% 초소형 사이즈 S빔 타입 	LSB-200 (L2357)
LTH-300 (L2760) 	<ul style="list-style-type: none"> 도너츠 타입 	LTH-300 (L2760)
LLB-302 (L1630) 	<ul style="list-style-type: none"> 초소형 버튼 타입 	LLB-302 (L1630)
L2900 	<ul style="list-style-type: none"> Range: 300lbs~250Klbs 팬케이크 타입 	L2900



Sensor Development (미국)



Products	Features (특징)	Link
01324 시리즈 로터리 토크센서	<ul style="list-style-type: none"> 정밀도: 0.1% 최대 5000RPM 	01324
90061 용접 하중 측정센서		90061
기타 하중 센서		Others

Honeywell Honeywell: 센서 종합 메이커

